

Declaration of compliance

29395 - Stainless Steel Handle, 1500mm, White Item number:

Vikan A/S Business operator:

> Rævevej 1 7800 Skive Denmark

Tel.: +45 96 14 26 00

Materials: Polypropylene 97 %, white masterbatch 2 % and foamer 1% in the handle.

Monomers and additives used to manufacture this grade are listed in Commision Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011), 1183/2012 (30. November 2012) and 202/2014 (3. March 2014) are included.

No monomers with specific migration limit (SML) are used. Additives with specific migration limit are used.

This material contains one or more dual use additives. The identity of this/these substance(s) can be disclosed for testing purposes upon special request. Further information can be given on request.

White masterbatch and foamer

Monomers and additives used to manufacture this grade are listed in Commision Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011), 1183/2012 (30. November 2012) and 202/2014 (3. March 2014) are included.

Following monomers and additives with specific migration limit (SML) are used in the white masterebatch: Ref no. 13380/25600/94960, cas no. 77-99-6, 1,1,1-trimethylolpropan and ref. no 68320, cas no. 2082-79-3, octadecyl-3-(3,5-di-tert-butyl-4- hydroxyphenyl) propionat.

Calculations have proven that the product meets the requirement regarding the SML.

Dual use additives: Ref. no. 42500 Carbonic acid salts and Ref. no. 86240 Anti-blocking

Regarding the foamer following additives with specific migration limit (SML) are used: Vinyl acetat, Cas no. 108-05-4 with SML 12.00 mg/kg and 2,6-Di-tert-Butyl-p-cresol (BHT), Cas no. 128-37-0 with SML 3.00

The product meets the requirement regarding SML for both materials either by product test (Vinyl acetate) or by calculation (BHT).

The tube is produced from stainless steel AISI 304 according to EU Commission Regulation no. 2023/2006 (GMP) and in compliance with EU Commission Regulation no. 1935/2004.

All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) CFR

In accordance with EU Commission Regulation no. 1935/2004 of October 2004 the product is intended for EU Commission:

food contact. The squeegee can be marked with the "glass & fork" symbol on the packaging or on the

product itself through moulding.

The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Overall migration tests are made on similar products. The products meet the requirements regarding

overall migration to 50 % ethanol, 3 % acetic acid and olive oil.

No limitation Food contact:

FDA:

Min. temp.: -20 °C Usage temperature:

Max. temp.: 80 °C

General: It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to it's intended use,

It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the

appropriate decontamination chemicals, concentrations, times and temperatures

Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination

and will maximise the efficiency and durability of the equipment.

Max. Wash temp.: 121 °C

10th September 2014 Date

Inger Arensbach Made by:

Quality- and environmental manager