



## Declaration of compliance - Only FDA

Item number: 42885  
Item name: Brush with heat resistant plastic filaments, 255mm, White

Producer: **Vikan A/S**  
Rævevej 1  
7800 Skive  
Denmark  
Tel.: +45 96 14 26 00

Materials: **Polypropylene 97 %, white masterbatch 2 % and foamer 1% in the brush block.**

### **Polypropylene:**

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011) and 1183/2012 (30. November 2012) are included.

This polypropylene grade contains the following "dual use" additives: Glycerol monostearat, calcium stearat and talc.

No monomers and additives with specific migration limit (SML) are used.

### **White masterbatch and foamer:**

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011) and 1183/2012 (30. November 2012) are included.

White masterbatch contains the following "dual use" additive: TiO<sub>2</sub>.

### **Filaments made from Polyaryletheretherketone polymer (PEEK)**

PEEK is produced according to FDA CFR 21 177.2415 and may be used for food contact purposes.

### **Stainless steel thread**

No restrictions or specific migration levels.

FDA: All raw materials in this product are in compliance with FDA (Food and Drug Administration in the U.S.) CFR 21.

EU Commission: The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2011 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Food contact: No limitation

Usage temperature: Min. temp.: -20 °C  
Max. temp.: 230 °C


General: It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to its intended use, before use.

It is also important to clean, disinfect and sterilise equipment after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise risk of microbial growth and cross contamination and maximise the efficiency and durability of the equipment.

Recommended wash temp.: 121 °C

Date: 22nd November 2018

Made by:   
Inger Arensbach  
Quality- and environmental manager