



## Declaration of compliance

Regarding following item: 77226 - Hygienic Revolving Neck Squeegee w/replacement cassette, 405 mm, Yellow  
77236 - Hygienic Revolving Neck Squeegee w/replacement cassette, 505 mm, Yellow  
77246 - Hygienic Revolving Neck Squeegee w/replacement cassette, 600 mm, Yellow  
77256 - Hygienic Revolving Neck Squeegee w/replacement cassette, 700 mm, Yellow

Business operator: **Vikan A/S**  
Rævevej 1  
7800 Skive  
Denmark  
Tel.: +45 96 14 26 00

Materials: **Polypropylene 98 %**  
Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011, 1282/2011, 1183/2012 and 202/2014 are included.

No monomers with specific migration limit (SML) are used. Additives with specific migration limit are used.

This material contains one or more dual use additives. The identity of this/these substance(s) can be disclosed for testing purposes upon special request.  
Further information can be given on request.

### **The squeegee blade for 2C made from rubber 98 %**

The Styrene Block Copolymer, the polypropylene resin and ethylene-vinyl acetate copolymer (EVA), used in the construction of this equipment, meet the relevant requirements of Framework Regulation 1935/2004/EC, with regard to plastic raw materials used for articles or components of articles intended to come into contact with food. The monomers, starting substances and additives (incl. the plasticiser) used are listed in Annex I of the consolidated Commission Regulation No.10 (2011), related to Plastic Materials and Articles intended to come into contact with foodstuffs). The mineral filler complies with EN71-3.

Applicable restrictions are available on request (supplier proprietary information).

### **Yellow masterbatch 2 %**

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011, 1282/2011, 1183/2012 and 202/2014 are included.

Following monomers and additives with specific migration limit (SML) are used in the yellow masterbatch: Ref no. 13380/25600/94960, cas no. 77-99-6, 1,1,1-trimethylolpropan and ref. no 68320, cas no. 2082-79-3, octadecyl-3-(3,5-di-tert-butyl-4- hydroxyphenyl) propionat. Calculations have proven that the product meets the requirement regarding the SML.

Following dual use additives are used: Carbonic acids (salts), Silicon dioxide and Stearic acid.

---

FDA: All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) CFR 21.

EU Commission: In accordance with EU Commission Regulation no. 1935/2004 of October 2004 the product is intended for food contact. The squeegee can be marked with the "glass & fork" symbol on the packaging or on the product itself through moulding.

The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Overall migration tests are made on similar products:

The test made on 3% Acetic acid for 15 minutes at 50 °C complies with the requirements in EU 10/2011.

The test made on 50% Ethanol for 15 minutes at 50 °C complies with the requirements in EU 10/2011.


The test made on olive for 15 minutes at 50 °C does not comply with the requirements in EU 10/2011

Usage temperature: Min. temp.: -20 °C  
Max. temp.: 50 °C

General: It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to its intended use, before use.  
It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.  
Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.

Max. Wash temp.: 121 °C

Date: 18th December 2014

Made by:   
Inger Arensbach  
Quality- and environmental manager